

# SL-58X-T30-5050-RGB-12V-5M

## LED Flexible Lighting Strip

### *Data Sheet*





**5 Meter, 30pcs 3 in 1 RGB 5050 LEDs/meter, DC12V**  
 Could be cut to 50 sections, 100mm with 3pcs TOP LEDs per section.

## Feature:

1. 3 colored chips (RGB) in one packaged 5050 TOP LEDs.
2. All chips are made in Taiwan; Provide Incomparable brightness in the small dimension.
3. Flexible PC Board with 3M tape at the back side, easy installation.
4. Double side copper foil in flexible PC to offer good heat sink.

Note: Do unfold the flexible PC before turn on the LED.

Specification						
Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Emitting Color				R-G-B		
Wavelength,				625nm-525nm-470nm		
LED No.				3 in 1 RGB		
Beam Angle				120		
Input Voltage	Vop	DC		12		V
LED Current	I	DC12V		2916		mA
Power Watts	Po	DC12V		35		W
Luminous Flux	øv	DC12V		750		Lm
Connector				4 PIN VCC-R-G-B		
Dimension		5000mm x 12mm, 150 LEDs/Roll				
		100mm x 12mm, 3 LEDs/Section				
Operating Temp.	T			-4~45		°C
Net weight	Wg			130		G