

SL-58X-T30-5050-XX-12V-5M

LED Flexible Lighting Strip

Data Sheet





5 Meter, 30pcs 3 in 1 5050 LEDs/meter, DC12V
 Could be cut to 50 sections, 100mm with 3pcs TOP LEDs per section.

Feature:

1. 3chips in one packaged 5050 TOP LEDs.
2. All chips are made in Taiwan; Provide Incomparable brightness in the small dimension.
3. Flexible PC Board with 3M tape at the back side, easy installation.
4. Double side copper foil in flexible PC to offer good heat sink.

Note: Do unfold the flexible PC before turn on the LED.

Specification

	WW	OW	OR	OG	OB	OY	
Emitting Color	Warm White	Cool White	Red	Green	Blue	Amber	
Wavelength, Color temperature	2600-2800 K	6000-7000 K	625nm	525nm	470nm	590nm	
LED No.	150						
Beam Angle	120						
Input Voltage	12						V
LED Current	2916						mA
Power Watts	35						W
Luminous Flux	1750	1830	625	1455	290	540	Lm
Connector	2 pins						
Dimension	5000mm x 12mm, 150 LEDs/Roll 100mm x 12mm, 3 LEDs/Section						
Operating Temp.	-5~45						°C
Net weight	130						G



Cindi Enterprise Co., Ltd.

No.21 Min Shen E. Rd. Sec. 3, Taipei, Taiwan .

<http://www.cindi.com.tw/>

TEL: +886-2-2501-5211 FAX: +886-2-2501-1417

Page 2