

SL-58X-T60-5050-RGB-12V-5M

LED Flexible Lighting Strip

Data Sheet





5 Meter, 60pcs 3 in 1 RGB 5050 LEDs/meter, DC12V
 Could be cut to 100 sections, 50mm with 3pcs TOP LEDs per section.

Feature:

1. 3 colored chips (RGB) in one packaged 5050 TOP LEDs.
2. All chips are made in Taiwan; Provide Incomparable brightness in the small dimension.
3. Flexible PC Board with 3M tape at the back side, easy installation.
4. Double side copper foil in flexible PC to offer good heat sink.

Note: Do unfold the flexible PC before turn on the LED.

Specification						
Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Emitting Color				R-G-B		
Wavelength,				625nm-525nm-470nm		
LED No.				3 in 1 RGB		
Beam Angle				120		
Input Voltage	Vop	DC		12		V
LED Current	I	DC12V		5833		mA
Power Watts	Po	DC12V		70		W
Luminous Flux	øv	DC12V		1500		Lm
Connector				4 PIN VCC-R-G-B		
Dimension		5000mm x 12mm, 300 LEDs/Roll				
		50mm x 12mm, 3 LEDs/Section				
Operating Temp.	T			-4~45		°C
Net weight	Wg			140		G