

SL-58X-T60-5050-XX-12V-5M

LED Flexible Lighting Strip

Data Sheet



5 Meter, 60pcs 3 in 1 5050 LEDs/meter, DC12V

Cindi Enterprise Co., Ltd..

21 Min Shen E. Rd. Sec.3, Taipei 104 Taiwan

<http://www.cindi.com.tw/>

L: +886-2-2501-5211 FAX: +886-2-2501-1417

Could be cut to 100 sections, 50mm with 3pcs TOP LEDs per section.

Feature:

1. 3chips in one packaged 5050 TOP LEDs.
2. All chips are made in Taiwan; Provide Incomparable brightness in the small dimension.
3. Flexible PC Board with 3M tape at the back side, easy installation.
4. Double side copper foil in flexible PC to offer good heat sink.

Note: Do unfold the flexible PC before turn on the LED.

Specification							
	WW	OW	OR	OG	OB	OY	
Emitting Color	Warm White	Cool White	Red	Green	Blue	Amber	
Wavelength, Color temperature	2600-2800 K	6000-7000 K	625nm	525nm	470nm	590nm	
LED No.	300						
Beam Angle	120						
Input Voltage	12 V						
LED Current	5833 mA						
Power Watts	70 W						
Luminous Flux	3500	3660	1250	2910	580	1080	Lm
Connector	2 pins						
Dimension	5000mm x 12mm, 300 LEDs/Roll 50mm x 12mm, 3 LEDs/Section						
Operating Temp.	-5~45 °C						
Net weight	140 G						

台光牌



Cindi Enterprise Co., Ltd..

No.21 Min Shen E. Rd. Sec.3, Taipei 104 Taiwan

<http://www.cindi.com.tw/>

TEL: +886-2-2501-5211 FAX: +886-2-2501-1417