



SL-818



I . Feature

- Accessible in a selection of LED light colors
- Compatible with light , easy use and installation
- Standard double-heart circuit to against UV
- Light and delicate appearance
- Low voltage operation at 90~240V AC
- Aluminum material which provides excellent thermal performance
- Beam angle at 30 degrees
- Satisfy the indoor lighting, as bright as Energy Saving Light Bulb
- Safety standard: CE
- No UV

II. Typical Applications

- Architectural lighting
- Boutique lighting
- Landscape lighting
- Indoor lighting
- Exhibition lighting

III. SPECIFICATION

- Operating Voltage: 90~240V AC
- Reserve of 30 cm double-heart circuit
- Heat Sink: Aluminum, stainless coil, and phosphor light-conductive cover
- Install 12 PCS High Power LED ,keep cool and get long longevity
- Operating Temp: -10~40°C
- Embedded Hole: 120mm
- Dimension: W150 H150

Mr-16 Power	Led	Lumi	Beam Angle	Color	Part No.
15W	11W	340-660	30°	Red	SL-818-R
18W	15W	600-660	30°	Green	SL-818-G
18W	15W	120-180	30°	Blue	SL-818-B
15W	11W	420-480	30°	Amber	SL-818-Y
18W	15W	960-1200	30°	Warm White	SL-818-WW
18W	15W	960-1200	30°	White	SL-818-W

Photometric

Ambient Operating Temperature, Tj = 25o

Color	Dominat Wavelength		Half-Width (nm)
	Min. (nm)	Max. (nm)	
Red	620	630	25
Green	520	530	35
Blue	460	470	25
Amber	585	595	25
White	6000K	7000K	
Warm White	2800K	3800K	

Version: CINDI SL-821 SPEC 990804